

Lecture 4: Frameworks/Models

Information Visualization
CPSC 533C, Fall 2006

Tamara Munzner

UBC Computer Science

21 September 2006

Papers Covered

Chapter 1, Readings in Information Visualization: Using Vision to Think. Stuart Card, Jock Mackinlay, and Ben Shneiderman, Morgan Kaufmann 1999.

The Structure of the Information Visualization Design Space Stuart Card and Jock Mackinlay, Proc. InfoVis 97
[citeseer.ist.psu.edu/card96structure.html]

The Eyes Have It: A Task by Data Type Taxonomy for Information Visualizations Ben Shneiderman, Proc. 1996 IEEE Visual Languages, also Maryland HCIL TR 96-13
[citeseer.ist.psu.edu/shneiderman96eyes.html]

Polaris: A System for Query, Analysis and Visualization of Multi-dimensional Relational Databases. Chris Stolte, Diane Tang and Pat Hanrahan, IEEE TVCG 8(1), January 2002.
[graphics.stanford.edu/papers/polaris]

The Value of Visualization. Jarke van Wijk. Visualization 2005
[www.win.tue.nl/vanwijk/vov.pdf]

Further Readings

Automating the Design of Graphical Presentations of Relational Information. Jock Mackinlay, ACM Transaction on Graphics, vol. 5, no. 2, April 1986, pp. 110-141.

Semiology of Graphics, Jacques Bertin, Gauthier-Villars 1967, EHESS 1998

The Grammar of Graphics, Leland Wilkinson, Springer-Verlag 1999

Rethinking Visualization: A High-Level Taxonomy Melanie Tory and Torsten Möller, Proc. InfoVis 2004, pp. 151-158.


Frameworks

- ▶ Shneiderman
 - ▶ Data, Tasks
- ▶ Mackinlay/Card/(Bertin)
 - ▶ Data Types, Marks, Retinal Attributes (incl Position)
- ▶ Stolte/Tang/Hanrahan, (Wilkinson)
 - ▶ Table Algebra \Leftrightarrow Visual Interface
- ▶ Hanrahan, Tory/Moeller
 - ▶ Data/Conceptual Models

Visual Language is a Sign System

- ▶ Image perceived as set of signs
- ▶ Sender encodes information in these signs
- ▶ Receiver decodes information from these signs

Visualization Big Picture




Mapping


- ▶ input
 - ▶ data semantics
 - ▶ use domain knowledge
- ▶ output
 - ▶ visual encoding
 - ▶ visual/graphical/perceptual/retinal
 - ▶ channels/attributes/dimensions/variables
 - ▶ use human perception
- ▶ processing
 - ▶ algorithms
 - ▶ handle computational constraints

Bertin: Semiology of Graphics

- ▶ geometric primitives: marks
 - ▶ points, lines, areas, volumes
- ▶ attributes: visual/retinal variables
 - ▶ parameters control mark appearance
 - ▶ separable channels flowing from retina to brain
- ▶ X,y
 - ▶ position
- ▶ Z
 - ▶ size
 - ▶ greyscale
 - ▶ color
 - ▶ texture
 - ▶ orientation
 - ▶ shape




Design Space = Visual Metaphors



[Bertin, Semiology of Graphics, 1967 Gauthier-Villars, 1998 EHESS]

Information in Position




1. **A, B, C are distinguishable**
2. **B is between A and C.**
3. **BC is twice as long as AB.**

"Resemblance, order and proportional are the three signfields in graphics." - Bertin

[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding/walk025.html]

Data Types


- ▶ continuous (quantitative)
 - ▶ 10 inches, 17 inches, 23 inches



Data Types


- ▶ continuous (quantitative)
 - ▶ 10 inches, 17 inches, 23 inches

- ▶ ordered (ordinal)
 - ▶ small, medium, large
 - ▶ days: Sun, Mon, Tue, ...



Data Types

- ▶ continuous (quantitative)
 - ▶ 10 inches, 17 inches, 23 inches
- ▶ ordered (ordinal)
 - ▶ small, medium, large
 - ▶ days: Sun, Mon, Tue, ...
- ▶ categorical (nominal)
 - ▶ apples, oranges, bananas



[graphics.stanford.edu/papers/polaris]


More Data Types: Stevens

- ▶ subdivide quantitative further:
- ▶ interval: 0 location arbitrary
 - ▶ time: seconds, minutes
- ▶ ratio: 0 fixed
 - ▶ physical measurements: Kelvin temp

[S.S. Stevens, On the theory of scales of measurements, Science 103(2684):677-680, 1946]

Channel Ranking Varies by Data Type

- ▶ spatial position best for all types



[Mackinlay, Automating the Design of Graphical Presentations of Relational Information, ACM TOG 5:2, 1986]

Mackinlay, Card

- ▶ Data Variables
 - ▶ 1D, 2D, 3D, 4D, 5D, etc
- ▶ Data Types
 - ▶ nominal, ordered, quantitative
- ▶ Marks
 - ▶ point, line, area, surface, volume
 - ▶ geometric primitives
- ▶ Retinal Properties
 - ▶ size, brightness, color, texture, orientation, shape...
 - ▶ parameters that control the appearance of geometric primitives
 - ▶ separable channels of information flowing from retina to brain
- ▶ closest thing to central dogma we've got

Shneiderman's Data+Tasks Taxonomy

- ▶ Data
 - ▶ 1D, 2D, 3D, temporal, nD, trees, networks
 - ▶ text and documents (Hanrahan)
- ▶ Tasks
 - ▶ Overview, Zoom, Filter, Details-on-demand,
 - ▶ Relate, History, Extract
- ▶ data alone not enough
 - ▶ what do you need to do?

[Shneiderman, The Eyes Have It: A Task by Data Type Taxonomy for Information Visualizations]

Data Models vs. Conceptual Models

- ▶ data model: mathematical abstraction
 - ▶ set with operations
 - ▶ e.g. integers or floats with $*$, $+$
- ▶ conceptual model: mental construction
 - ▶ includes semantics, support data
 - ▶ e.g. navigating through city using landmarks

[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding/walk005.html]

Models Example

- ▶ from data model
 - ▶ 17, 25, -4, 28.6
 - ▶ (floats)

Models Example

- ▶ from data model
 - ▶ 17, 25, -4, 28.6
 - ▶ (floats)
- ▶ using conceptual model
 - ▶ (temperature)

Models Example

- ▶ from data model
 - ▶ 17, 25, -4, 28.6
 - ▶ (floats)
- ▶ using conceptual model
 - ▶ (temperature)
- ▶ to data type
 - ▶ burned vs. not burned (N)
 - ▶ hot, warm, cold (O)
 - ▶ continuous to 4 sig figures (Q)

Models Example

- ▶ from data model
 - ▶ 17, 25, -4, 28.6
 - ▶ (floats)
- ▶ using conceptual model
 - ▶ (temperature)
- ▶ to data type
 - ▶ burned vs. not burned (N)
 - ▶ hot, warm, cold (O)
 - ▶ continuous to 4 sig figures (Q)
- ▶ using task
 - ▶ making toast
 - ▶ classifying showers
 - ▶ finding anomalies in local weather patterns


Time

- ▶ 2D+T vs. 3D
 - ▶ same or different? depends on POV
 - ▶ time as input data?
 - ▶ time as visual encoding?
- ▶ same
 - ▶ time just one kind of abstract input dimension
- ▶ different
 - ▶ input semantics
 - ▶ visual encoding: spatial position vs. temporal change
- ▶ processing might be different
 - ▶ e.g. interpolate differently across timesteps than across spatial position

Polaris


- ▶ infovis spreadsheet
- ▶ table cell
 - ▶ not just numbers: graphical elements
 - ▶ wide range of retinal variables and marks
- ▶ table algebra \Leftrightarrow interactive interface
 - ▶ formal language
- ▶ influenced by Wilkinson
 - ▶ Grammar of Graphics, Springer-Verlag 1999

Polaris: Circles, State/Product:Month




[Polaris: A System for Query, Analysis and Visualization of Multi-dimensional Relational Databases. Chris Stolte, Diane Tang and Pat Hanrahan, IEEE TVCG, 8(1) Jan 2002]

Polaris: Gantt Bar, Country/Time




[Polaris: A System for Query, Analysis and Visualization of Multi-dimensional Relational Databases. Chris Stolte, Diane Tang and Pat Hanrahan, IEEE TVCG, 8(1) Jan 2002]

Polaris: Circles, Lat/Long



[Polaris: A System for Query, Analysis and Visualization of Multi-dimensional Relational Databases. Chris Stolte, Diane Tang and Pat Hanrahan, IEEE TVCG, 8(1) Jan 2002]

Polaris: Circles, Profit/State:Months




[Polaris: A System for Query, Analysis and Visualization of Multi-dimensional Relational Databases. Chris Stolte, Diane Tang and Pat Hanrahan, IEEE TVCG, 8(1) Jan 2002]

Fields Create Tables and Graphs

- ▶ Ordinal fields: interpret field as sequence that partitions table into rows and columns:
 - ▶ Quarter = (Qtr1),(Qtr2),(Qtr3),(Qtr4) \Leftrightarrow

Qtr1	Qtr2	Qtr3	Qtr4
95892	101760	105282	98225

- ▶ Quantitative fields: treat field as single element sequence and encode as axes:
 - ▶ Profit = (Profit) \Leftrightarrow



Combinatorics of Encodings

- ▶ challenge
 - ▶ pick the best encoding from exponential number of possibilities $(n + 1)^8$
- ▶ Principle of Consistency
 - ▶ properties of the image should match properties of data
- ▶ Principle of Importance Ordering
 - ▶ encode most important information in most effective way

[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding]

Automatic Design

- ▶ Mackinlay, APT
- ▶ Roth et al, Sage/Visage
- ▶ select visualization automatically given data
 - ▶ vs. Polaris: user drag and drop exploration
- ▶ limited set of data, encodings
 - ▶ scatterplots, bar charts, etc
- ▶ holy grail
 - ▶ entire parameter space



Mackinlay's Criteria

- ▶ Expressiveness
 - ▶ Set of facts expressible in visual language if sentences (visualizations) in language express **all** facts in data, and **only** facts in data.
- ▶ consider the failure cases...

[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding]

Cannot Express the Facts

- ▶ A 1 \Leftrightarrow N relation cannot be expressed in a single horizontal dot plot because multiple tuples are mapped to the same position



[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding]

Expresses Facts Not in the Data

- ▶ Length interpreted as quantitative value
 - ▶ Thus length says something untrue about nominal data




Fig. 11. Incorrect use of a bar chart for the *Nation* relation. The lengths of the bars suggest an ordering on the vertical axis, as if the USA cars were longer or better than the other cars, which is not true for the *Nation* relation.

[Mackinlay, APT]

Mackinlay's Criteria

- ▶ Expressiveness
 - ▶ Set of facts expressible in visual language if sentences (visualizations) in language express **all** facts in data, and **only** facts in data.
- ▶ Effectiveness
 - ▶ A visualization is more effective than another visualization if information conveyed by one visualization is more readily perceived than information in other.
 - ▶ subject of the next lecture

[[Hanrahan,graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding](http://Hanrahan.graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding)]


Summary

- ▶ formal approach to picture specification
 - ▶ declare the picture you want to see
 - ▶ compile query, analysis, and rendering commands needed to make the pictures
 - ▶ automatically generate presentations by searching over the space of designs
- ▶ Bertin's vision still not complete
 - ▶ formalize data model
 - ▶ formalize the specifications
 - ▶ experimentally test perceptual assumptions
- ▶ much more research to be done...

[Hanrahan, graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding]

Value of Vis

- ▶ $I(t) = V(D, S, t)$
 - ▶ data D transformed by spec S into time-varying image
- ▶ $dK/dt = P(I, K)$
 - ▶ perception P of image by user increases knowledge K
- ▶ $S(t) = S_0 + \int E(K)$
 - ▶ interactive exploration E changes spec



Cost Model

- ▶ costs

- ▶ $C_i(S_0)$: initial development costs
- ▶ $C_u(S_0)$: initial per-user costs
- ▶ $C_s(S_0)$: initial per-session costs
- ▶ C_e : perception and exploration costs

- ▶ benefit

- ▶ $G = nmW(\Delta K)$

- ▶ profit

- ▶ $F = G - C$

- ▶ $F = nm(W(\Delta K) - C_s - kC_e) - C_i - nC_u$

“a great visualization method is used by many people, who use it routinely to obtain highly valuable knowledge, without having to spend time and money on hardware, software, and effort. Indeed, quite obvious.”

Arguments

- ▶ new methods not better by definition
- ▶ vis not good by definition
 - ▶ must show why automated extraction insufficient
 - ▶ e.g. automation not foolproof
- ▶ if no clear patterns
 - ▶ method limitation?
 - ▶ wrong parameters?
 - ▶ or truly not there in data?
- ▶ inspire new hypotheses vs. verify final truth

Arguments

- ▶ “avoid interaction” dictum controversial
 - ▶ part of power of computer-based methods
 - ▶ but can degenerate into human-powered search
- ▶ presentation/exposition vs. exploration
- ▶ art vs. science vs. technology

Credits

- ▶ Pat Hanrahan
 - ▶ graphics.stanford.edu/courses/cs448b-04-winter/lectures/encoding
- ▶ Torsten Möller, Melanie Tory
 - ▶ discussions